



Henkel

DORUS® KS 250 COOL The COOL Edge Banding Adhesive

Your Benefits

- Edge banding of the future
- Low application temperature: 140 °C – 150 °C
- Clean Processing
- Higher operational safety due to lower working temperature
- Thin glue line





DORUS® KS 250 COOL **NEW**

The COOL Edge Banding Adhesive

Bonding with Low Application Temperature: 140 °C – 150 °C

Advantages during Processing:

- Thin glue line
- Reduction of coating weights
- Clean processing – no stringing
- High thermal stability
- No smoke emission
- No thermal degradation during downtimes
- No drop of working temperature during downtimes necessary
- Higher operational safety due to lower working temperature
- Reduced maintenance costs
- Reduced energy costs

Range of Application:

- Edge banding (straight edges)
- Softforming
- Feed rate of 12 – 90 m/min.
- For paper edges and thermoplastic edges up to 3 mm
- High bond strength of the adhesion
- Good heat resistance

Convince yourself of the quality of our innovation. Practical trials with DORUS® KS 250 COOL can be arranged. Please contact us to make an appointment.

Contact

Henkel AG & Co. KGaA
Kirchheimer Strasse 9
73441 Bopfingen, Germany
Phone +49 (0)7362 81-0
Fax +49 (0)7362 81-199
E-mail dorus.henkel@henkel.com
www.dorus.com